# Tornado OTR tyres now in stock!



## **G-2 GRADER**

- For quarry & construction applications on soft, muddy and sandy terrain
- High traction directional pattern
- Thick tread shoulder design Optimised belt structure for excellent cut resistance
- Excellent self-cleaning

Size	Ply	Type	Grade
14.00-24TG	16	TLS BIAS	G2

## **GLR82-G2 GRADER**

- Tread pattern provides excellent traction, handling and ride comfort
- Extra deep tread for longer tread life
- and tread compound for excellent cut resistance

	Star		
Size	Rating	Type	Grade
14.00R24	*	TLS	G2

## E3/L3 HRL BIAS

- For rough roads e.g. mining and construction sites
- Hard Rock Lug (HRL), nondirectional and deep tread pattern
- Excellent grip, traction and
- High strength carcass
- Puncture, cut and wear resistant compound

Size	Ply	Туре	Grade
17.5-25	20	TLS BIAS	E3/L3
20.5-25	20	TLS BIAS	E3/L3
23.5-25	20	TLS BIAS	E3/L3

## **GLR09 RADIAL E3/L3**

- Lug pattern provides excellent traction, grip and super stable handling
- Strengthened carcass and reinforced bulking protection sidewall for better puncture and scratch resistance
- Optimised contact area and compound provides excellent wear resistance for extended service life

Size	Star Rating	Туре	Grade
17.5R25	**	TLS	E3/L3
20.5R25	**	TLS	E3/L3
23.5R25	**	TLS	E3/L3
26.5R25	**	TLS	E3/L3
29.5R25	**	TLS	E3/L3



