Earthmover tyres now in stock!

GLR09 RADIAL E3/L3

- Excellent traction, grip and super stable handling
- Strengthened carcass and reinforced bulking protection sidewall for better puncture and scratch resistance
- Optimised contact area and compound provides excellent wear resistance for extended service life.

Size	Rating	Type	Grade
17.5R25	**	TLS	E3/L3
20.5R25	**	TLS	E3/L3
23.5R25	**	TLS	E3/L3
26.5R25	**	TLS	E3/L3
29.5R25	**	TLS	E3/L3



GLR08 RADIAL L5

- Directional tread design for superior grip and traction on a variety of surfaces
- Optimised tread shoulder for improved stability and control
- Special sidewall compound protects against cuts and punctures, increasing the tyre's resilience and reducing downtime due to tyre damage.

Size	Rating	Туре	Grade
17.5R25	**	TLS	L5
29.5R25	**	TLS	



E3/L3 HRL BIAS

- For rough roads e.g. mining and construction sites
- Hard Rock Lug (HRL), non-directional and deep tread pattern
- Excellent grip, traction and control
- High strength carcass
- Puncture, cut and wear resistant compound.

Size	Ply	Туре	Grade
17.5-25	20	TLS BIAS	E3/L3
20.5-25	20	TLS BIAS	E3/L3
23.5-25	20	TLS BIAS	E3/L3



ORDER NOW! CALL YOUR LOCAL NETA BRANCH:

CAIRNS 4242 1160 ROCKHAMPTON 4927 1251 SUNSHINE COAST 5445 6337

BRISBANE 3552 2800 GOLD COAST 5594 0963 TOOWOOMBA 4634 9238 LISMORE

(02) 6621 5131

neta.com.au



Earthmover tyres now in stock!



G-2 **GRADER**

- For construction and quarry applications on soft, muddy and sandy terrain
- High traction directional pattern
- Thick shoulder design for excellent cut resistance
- Excellent self-cleaning

Size	Ply	Type	Grade
14.00-24TG	16	TLS BIAS	G2



GLR82-G2 GRADER

- Excellent traction, handling and ride comfort
- Extra deep tread for longer tread life
- Optimised belt structure and tread compound for excellent cut resistance.

Size	Rating	Туре	Grade
14.00R24	*	TLS	G2



CAIRNS ROCKHAMPTON 4927 1251 **GOLD COAST** 5594 0963

4242 1160 **BRISBANE** 3552 2800 **SUNSHINE COAST** 5445 6337 **TOOWOOMBA** 4634 9238

LISMORE

(02) 6621 5131

neta.com.au

